

## TECHNICAL DATA SHEET BUTYL BAND

### DESCRIPTION

Adhesive cold butyl band designed to assure an optimum repair in leaks of air as well as of water. It is composed by a coat of butyl adhesive and a coating of aluminium alloy protected against the outdoor conditions.

### INSTRUCTIONS

The installation surface must be dry and clean, without grease nor dust. In case of replacing the butyl band, clean remains and degrease with a solvent. For an application between 0°C and +5°C, it is convenient to assure the previous absence of frost or of condensation. Position the product, detaching the protector and placing the butyl band on the surface, avoiding the formation of air bubbles.

### APPLICATION AND CONSUMPTION

It can be applied on fibre concrete, PVC, and on other types of nonporous materials. Respect a length of coating that surpasses at least 5 cm. It can be painted.

Thanks to its versatility can be used for:

- Repairing drainpipes and joints.
- Sealing stained-glass windows, clerestories and chimney.
- Waterproofing covers and terraces.

In case of using it as waterproof, make sure that there is not risk of water retention.

### PRESENTATION

It comes in rolls of 10 cm. x 10 mts. Boxes of 8 units.

### STORAGE

The rolls can be stored up to 12 months in their original container. Store in dry places and to maximum temperature of 30°C.

### RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

### NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.